CERTIFICADO ◆ 인증서 ◆ CERTIFICATO ◆ 認証書 ◆ CERTIFICATE ◆ 认证证书 ◆ ZERTIFIKAT

C E R T I F I C A T E

No. Z1A 048890 0027 Rev. 00

Holder of Certificate: **Legamaster International B.V.**
Product Management Lochem
Kwinkweerd 62
7240 AC Lochem
THE NETHERLANDS

Certification Mark:

Product: **Height adjustable standing system for monitors**

Tested according to: EK5/AK7 18-02:2018
AfPS GS 2019:01 PAK

With this certificate, in its capacity as a notified GS body, TÜV SÜD Product Service GmbH issues the GS Mark to the named certificate holder for the declared product with the named model designation in accordance with section 20 ProdSG (German Product Safety Act). The product meets the safety and health requirements of section 20 (3) ProdSG. The manufacturer is reminded of their obligations in accordance with section 24 ProdSG. The certification marks shown above can be affixed on the product. It is not permitted to alter the certification marks in any way. In addition, the certificate holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the Testing, Certification, Validation and Verification Regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 713404199-1

Valid until: 2031-06-10

Date, 2026-06-12

(Michael Weber)

TÜV SÜD Product Service GmbH • Certification Body • Ridlerstraße 65 • 80339 Munich • Germany

CERTIFICADO ◆ 인증서 ◆ CERTIFICATO ◆ 認証書 ◆ CERTIFICATE ◆ 认证证书 ◆ ZERTIFIKAT

C E R T I F I C A T E

No. Z1A 048890 0027 Rev. 00

Model(s): **MOTION DYNAMIC Mobile Stand**
MOTION DYNAMIC Column System

Parameters:

MOTION DYNAMIC Mobile Stand	
Shape	Mobile system for monitors
Column	Linak DL6000BNE980730
Control unit	Linak CBD6SP00020A-009
Control element	Linak DPF1K00-010006
Total height [mm]	1064 - 1850; Δ780
Profile of the actuator columns [mm]	80x50; 73.5x43.5; 67x37
Maximum load capacity	min. VESA 200x200 max. VESA 600x800 max. 126 kg max. 249 cm (98") screen size
Material	frame: metal, black powder coated

MOTION DYNAMIC Column System	
Shape	Stand with wall mounting
Column	Linak DL1200xB0E660545
Control unit	Linak CBD6SP00020A-009
Control element	Linak DPF1K00-010006
Dimensions of side panels [mm]	1150x980
Total height [mm]	1470 - 2130; Δ660
Profile of the actuator columns [mm]	80x50; 73.5x43.5; 67x37
Maximum load capacity	min. VESA 200x200 max. VESA 600x800 max. 126 kg max. 249 cm (98") screen size
Material	frame: metal, black powder coated side panels: aluminium with enamel coating

TÜV SÜD Product Service GmbH • Certification Body • Ridlerstraße 65 • 80339 Munich • Germany